

FOUR-, SIX-CHANNEL EMI FILTER WITH ESD PROTECTION FOR LCD DISPLAY

 Check for Samples: [TPD4F202](#), [TPD6F202](#)

FEATURES



- Four-, Six-Channel EMI Filtering and ESD Protection for Data Lines
- Excellent filter Performance
 - >40dB Attenuation at 1GHz-3GHz
 - -3dB Bandwidth at 108MHz
 - 70 dB Crosstalk Attenuation at 100 MHz
- Exceeds IEC61000-4-2 (Level 4) ESD Protection Requirements
 - ±25-kV IEC 61000-4-2 Contact Discharge
 - ±25-kV IEC 61000-4-2 Air-Gap Discharge
 - ±15-kV Human-Body Model (HBM)
- Pi-Style C-R-C Filter Configuration Offers Symmetric Filter Performance

 (R = 100 Ω, C_{TOTAL} = 30 pF)

- Low 10-nA Leakage Current
- Space-Saving WCSP Package and Flow-Through Pin Mapping Provides Optimum Performance in Portable Applications

APPLICATIONS

- LCD Display Interface
- Memory Interface
- SVGA Video Connections
- Keypad
- Data Lines in Portables



ORDERING INFORMATION

T _A	PACKAGE ⁽¹⁾ (2)	PACKAGE DIMENSION	ORDERABLE PART NUMBER	TOP-SIDE MARKING
-40°C to 85°C	WCSP – YFU	Length = 2.36 mm, Width = 1.053 mm, Pitch = 0.4 mm, Height = 0.32 mm)	TPD6F202YFUR	YMS5WS
		Length = 1.56 mm, Width = 1.053 mm, Pitch = 0.4 mm, Height = 0.32 mm)	TPD4F202YFUR	YMS57S

- (1) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at www.ti.com.
- (2) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

DESCRIPTION

The TPDxF202 are four, six-channel EMI filters, designed particularly to suppress EMI noise in the cell phone and other portable applications. These low-pass filters also protect internal core circuitry against system level ESD strikes at the external interface pins. The pi-style C-R-C filter provides symmetric filter performance in the data lines to/ from either side of the filter.


Due to tiny package parasitics of the WCSP package, the TPDxF202 series of filters provide excellent signal attenuation (-40dB at 1GHz) at the typical cell-phone carrier frequency ranges.

The ultra thin (0.3-mm package height, when mounted on board) space saving YFU package enables the TPDxF202 devices to mount on the printed circuit boards where the height is a key constraint.

The TPDxF202 devices offer very robust system level ESD protection specifications at both input and output ports, which eliminates the need for any additional ESD clamp diodes at the external interface pins.

The TPDxF202 devices are specified for -40°C to 85°C operation.

EQUIVALENT SCHEMATIC REPRESENTATION



ABSOLUTE MAXIMUM RATINGS⁽¹⁾

over operating free-air temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V_{IO}	IO to GND		6	V
	Continuous power dissipation ($T_A = 70^\circ\text{C}$)		100	mW
T_{stg}	Storage temperature range	-65	150	$^\circ\text{C}$
T_J	Junction temperature		150	$^\circ\text{C}$
	Lead temperature (soldering, 10 s)		300	$^\circ\text{C}$

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rated conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

$T_A = -40^\circ\text{C}$ to 85°C (Unless otherwise noted)

PARAMETER	TEST CONDITIONS	MIN	TYP ⁽¹⁾	MAX	UNIT
V_{BR}	DC breakdown voltage	$I_{IO} = 10\ \mu\text{A}$	6		V
R	Resistance		85	100 115	Ω
C	Capacitance (C1 or C2)	$V_{IO} = 3.3\ \text{V}$	15		pF
I_{IO}	Channel leakage current	$V_{IO} = 3.3\ \text{V}$	10		nA
f_C	Cut-off frequency	$Z_{SOURCE} = 50\ \Omega, Z_{LOAD} = 50\ \Omega$	108		MHz

- (1) Typical values are at $T_A = 25^\circ\text{C}$.

ESD PROTECTION

PARAMETER	TYP	UNIT
HBM	± 15	kV
IEC 61000-4-2 Contact Discharge	± 25	kV
IEC 61000-4-2 Air-Gap Discharge	± 25	kV

APPLICATION INFORMATION

Typically, there are multiple EMI filters being utilized in cell phone applications to suppress the EMI interference. This means the total board area consumed by EMI filters are relatively large. One example of space saving innovation is to place the EMI filters right under the connectors so that the main PCB space is not utilized. The YFU packages of the TPDxF202 series offer ultra low-profile package height which enables such innovative component placement in portable applications. Package under-fill is recommended while using the YFU packages in flex boards.

For maximum efficiency of filtering and ESD protection, while doing the board layout, care should be taken to reduce board parasitic from package GND pins to board GND plane. The TPDxF202 devices should be connected to a ground plane with a micro via adjacent to the device GND pad. If this is not possible, the connection to the ground plane should be as direct as possible to minimize the inductance. Due to flow-through pin mapping, the signal pins routing is easily achieved in a single layer.




Figure 1. Board Layout with TPDxF20

TYPICAL CHARACTERISTICS




Figure 2. Channel-to-Channel Crosstalk




Figure 3. Frequency Response Data (0 V Bias)

TYPICAL CHARACTERISTICS (continued)




Figure 4. IEC Clamping Waveforms +8 kV Contact




Figure 5. IEC Clamping Waveforms -8 kV Contact

TYPICAL CHARACTERISTICS (continued)




Figure 6. DC Characteristics (I_{IN} vs. V_{IN}), $T_A = 25^\circ C$




Figure 7. C1 or C2 Capacitance vs. V_{BIAS}

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/ Ball Finish	MSL Peak Temp ⁽³⁾	Samples (Requires Login)
TPD4F202YFUR	PREVIEW	DSBGA	YFU	10	3000	TBD	Call TI	Call TI	Samples Not Available
TPD6F202YFUR	PREVIEW	DSBGA	YFU	15		TBD	Call TI	Call TI	Samples Not Available

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSELETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.


Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

MECHANICAL DATA

YFU (R-XBGA-N15)

DIE-SIZE BALL GRID ARRAY




- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. NanoFree™ package configuration.
 - D. This is a Pb-free solder ball design.

NanoFree is a trademark of Texas Instruments.

MECHANICAL DATA

YFU (R-XBGA-N10)

DIE-SIZE BALL GRID ARRAY



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. NanoFree™ package configuration.
 - D. This is a Pb-free solder ball design.

NanoFree is a trademark of Texas Instruments.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DLP® Products	www.dlp.com	Communications and Telecom	www.ti.com/communications
DSP	dsp.ti.com	Computers and Peripherals	www.ti.com/computers
Clocks and Timers	www.ti.com/clocks	Consumer Electronics	www.ti.com/consumer-apps
Interface	interface.ti.com	Energy	www.ti.com/energy
Logic	logic.ti.com	Industrial	www.ti.com/industrial
Power Mgmt	power.ti.com	Medical	www.ti.com/medical
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
RFID	www.ti-rfid.com	Space, Avionics & Defense	www.ti.com/space-avionics-defense
RF/IF and ZigBee® Solutions	www.ti.com/lprf	Video and Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless-apps

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2010, Texas Instruments Incorporated