



Never stop thinking

[Home](#) > [Microcontrollers](#) > [Development Tools, Software and Training](#) > [TriCore® Development Tools and Software](#) > [StarterKits and Evaluation Boards](#) > **SK-TC176x Family Starter Kit**

# SK-TC176x Family Starter Kit

## MCU Derivates:

SAK-TC1766-192F80HL  
SAK-TC1764-128F80HL  
SAK-TC1762-128F80HL  
SAK-TC1762-128F66HL

(The Family Starter Kit is equipped with the SAK-TC1766-192F80HL as superset for the TC176x family)

**CPU Clock:** 80 MHz

## On-Chip Memory:

- 1.5 MByte embedded program flash with ECC,
- 32 KByte data flash for scalable EEPROM emulation,
- 76 KByte on-chip SRAM,
- 8 KByte instruction cache.

## Interfaces:

- DB9 for RS232-0,
- BERG10 for RS232-1,
- two BERG10 for CAN-0/1 with Transceiver,
- BERG16 for OCDS1,
- SAMTEC QSH-030-01-F-D-A for OCDS2,
- DB25 On Board Wiggler for OCDS1,
- four 80-pin connectors (male) with all I/O signals,
- four 80-pin connectors (female) with all I/O signals.

## Includings:

- Technical Documentation: e.g. User manuals (System Unit and Peripheral unit), Architecture manual (pdf-version),
- Evaluation Versions of Development Tools: e.g. Compiler, Debugger, Operating System from Tool Partners,
- parallel cable,
- Extension Board,
- Starter Kit Manual, last Version 1.0.

**Order Nr.:** B158-H8539-G2-X-7600

**Price\*:** 400,- EUR

## How to order?

[Buy Online](#)

or please contact your local distributor: <http://www.infineon.com/distribution>.

\* recommended retail price.